

- Products**
- ▶ Active BNC
 - ▶ Connectors
 - ▶ HFO Interfacing
 - ▶ Optical Products
 - ▶ Cable
 - ▶ PatchBays
 - ▶ Assemblies
 - ▶ Cable Reels
 - ▶ Tools

- Distributor Listing**
- Catalog
 - Tech Notes
 - FAQ

▶ **Twisted Pair Microphone Cable (L-2B2AT)**



Product Name

Twisted Pair Microphone Cable

Model Number

L-2B2AT

Canare's thinnest profile audio hookup wire. Amazingly flexible, with 100% foil shield, drain wire and PVC jacket that strips easily for rapid assembly. Suitable for large cable harness bundles, mixing consoles, tape machines and inner-rack wiring.

Product Image

Applications

- ▶ Microphones
- ▶ Permanent Installations
- ▶ Audio Patch Cords
- ▶ PA Systems
- ▶ Post Production Suites
- ▶ Recording Studios

Features

- ▶ 100% Foil Shield Coverage w/Drain Wire
- ▶ Built in Dupont® Kevlar 29 and Drain Wire
- ▶ Cross Linked PE Insulation
- ▶ Reduced Handling Noise
- ▶ Rejects EMI and RFI

MECHANICAL SPECIFICATIONS										
Model	Std. Lng. ft. (m)	Wt Std. Lng. lbs (kgs)	Nom. O.D. in. (mm)	Jacket Nom. Thick. in. (mm)	Brittle Point F _o (C°)	No. of Cond.	Insul. Type* Thick mil	Cond-AWG (Qty./mil) Cross Sec. Area mil. ²	Pitch Twist Quad in. (mm)	Shield Coverage
L-2B2AT	656 (200)	6 (3)	.126 (3.2)	.012 (0.3)	-13 (-25)	2	IPE 12.6	AC - #25 (16/4.73) 279	<0.99 (<25)	100% Alum. Tape
	1640 (500)	15 (7)								

*Dielectric Strength = 500V AC/1min. Insulation Resistance/3Mft = >1000M ohm.

**Effective AWG of combined twin conductors.

ELECTRICAL PERFORMANCE							
Model	Cond. D.C.R. ohm/1000ft (ohm/100m)	Shield D.C.R. ohm/1000ft (ohm/100m)	Nom. Cap. *** pF/ft (pF/m)	Nom. Cap. † pF/ft (pF/m)	Nom. Imp. ohm	Nom. Atten. V/1000ft (V/100m)	Group Delay Time nS/ft (nS/m)
L-2B2AT	<31.9 (<10.5)	-	23 (73)	37 (120)	-	-	-

***Capacitance between conductors.

†Capacitance between conductors to shield.

COLORS AVAILABLE										
Model	Black	Blue	Brown	Gray	Green	Orange	Purple	Red	White	Yellow
L-2B2AT	[o]	--	--	[+]	--	--	--	--	--	--

[+]=Standard Color, [o]=Available Color, "--"=n/a